FILE NOTATIONS	The second secon	ann
Entered in NID File	Checked by Chief	4
Entered On S R Sheet	Copy N D to Field Office	
Location Map Pinned	Approval Letter	***********************
Card Indexed	Disapproval Letter	************************
I W R for State or Fee Land		
COMPLETION DATA:		
Date Well Completed 2-6-65	Location Inspected	46 40 E0 6 E E E E E E E E E E E E E E E E E
OW WW TA	Bond released	
GW OS PA	State of Fee Land	416291276120663688216148
	FILED	
Driller's Log 6-//-65		
Electric Logs (No.)	<u></u>	*.
	GR GR-N	Micro,
1_1 \A : 1 \$.	onic Others Others	ation) len

(SUBMIT IN DUPLICATE)

LAND:

	Х	_


STATE OF UTAH OIL & GAS CONSERVATION COMMISSION

SALT LAKE CITY, UTAH

Fee and Patented
State
Lease No
Public Domain
Lease No
Indian
Loope Me

Inting of Intention to Dail	
Notice of Intention to Drill	
Notice of Intention to Change Plans	Subsequent Report of Altering Casing
Notice of Intention to Redrill or Repair	
Notice of Intention to Pull or Alter Casing	Supplementary Well History
Notice of Intention to Abandon Well	
• • • • • • • • • • • • • • • • • • • •	NOVEMBER 18
A. J. Button Oil Unit "A"	WAFY (D)
Well No is located660 ft. from	November 18 , 19.6 om $\{S\}$ line and 1980 ft. from $\{E\}$ line of Sec. 20
) SE/4 Section 20 35 S (1/4 Sec. and Sec. No.) (Twp.)	3 E S.L.M. (Range) (Meridian)
(Field)	Garfield Utah (County or Subdivision) (State ar Territory)
	TAILS OF WORK is show sizes, weights, and lengths of proposed casings; indicate mud
jobs, cementing points, and all other important work, su	surface formation, and date anticipate spudding-in.)
1. Drill 15" hole to 250' and set and	nd cement 10-3/4" casing.
2. Drill to 4300' and set 7-5/8" cas:	sing with approximately 250 sacks cement.
2. Drill to 4300' and set 7-5/8" cas:	and cement 10-3/4" casing. Sing with approximately 250 sacks cement. O.) and set 5-1/2" casing with approximately
2. Drill to 4300' and set 7-5/8" cas:	sing with approximately 250 sacks cement.
2. Drill to 4300' and set 7-5/8" case 3. Drill to approximately 5000' (T.D.	sing with approximately 250 sacks cement.
2. Drill to 4300' and set 7-5/8" cas: 3. Drill to approximately 5000' (T.D. 150 sacks cement.	sing with approximately 250 sacks cement.
2. Drill to 4300' and set 7-5/8" cas: 3. Drill to approximately 5000' (T.D. 150 sacks cement.	sing with approximately 250 sacks cement.
2. Drill to 4300' and set 7-5/8" cas: 3. Drill to approximately 5000' (T.D. 150 sacks cement.	sing with approximately 250 sacks cement.
2. Drill to 4300' and set 7-5/8" cas: 3. Drill to approximately 5000' (T.D. 150 sacks cement.	sing with approximately 250 sacks cement.
2. Drill to 4300' and set 7-5/8" cas: 3. Drill to approximately 5000' (T.D. 150 sacks cement.	sing with approximately 250 sacks cement.
2. Drill to 4300' and set 7-5/8" cas: 3. Drill to approximately 5000' (T.D. 150 sacks cement.	sing with approximately 250 sacks cement.
2. Drill to 4300' and set 7-5/8" cas: 3. Drill to approximately 5000' (T.D. 150 sacks cement.	sing with approximately 250 sacks cement.
 2. Drill to 4300' and set 7-5/8" cas: 3. Drill to approximately 5000' (T.D. 150 sacks cement. 4. Perforate, acidize and test. 	sing with approximately 250 sacks cement.
 2. Drill to 4300' and set 7-5/8" cas: 3. Drill to approximately 5000' (T.D. 150 sacks cement. 4. Perforate, acidize and test. 	sing with approximately 250 sacks cement. O.) and set 5-1/2" casing with approximately oval in writing by the Commission before operations may be commen
2. Drill to 4300' and set 7-5/8" cas: 3. Drill to approximately 5000' (T.D. 150 sacks cement. 4. Perforate, acidize and test. I understand that this plan of work must receive approximately 5000' (T.D. 150 sacks cement.	sing with approximately 250 sacks cement. O.) and set 5-1/2" casing with approximately oval in writing by the Commission before operations may be comment

INSTRUCTIONS: A plat or map must be attached to this form showing the location of all leases, property lines, drilling and producing wells, within an area of sufficient size so that the Commission may determine whether the location of the well conforms to applicable rules, regulations and orders.



NOTE

ELEVATIONS SHOWN ON THIS PLAT WERE DETERMINED FROM A CLOSED LEVEL CIRCUIT FROM U.S. GEOLOGICAL SURVEY BENCH MARK 84 WF 1952.

175et Stoke. 2v. = 5786.7 1980'

ion For | DIL UNIT A-NO. 1 | lev. = 5785.8

> Found Brass Cap (1959 Survey)

20

6ARING) 29 23

CERTIFICATE

STATE OF UTAH COUNTY OF SEVIER

I HEREBY CERTIFY THAT THE ACCOMPANYING SKETCH IS A TRUE AND CORRECT PLAT OF A SURVEY MADE UNDER MY DIRECTION ON MOVEMBER 6, 1964, FOR TENNECO OIL COMPANY TO DETERMINE THE LOCATION OF A PROPOSED OIL WELL TO BE KNOWN AS A. J. BUTTON OIL UNIT A-No. 1; SAID LOCATION BEING 1980 FEET WEST OF THE EAST LINE AND 660 FEET NORTH OF THE SOUTH LINE OF SECTION 20, TOWN-SHIP 35 SOUTH, RANGE 3 EAST, SALT LAKE BASE & MERIDIAN, IN GARFIELD COUNTY, UTAH.

DATED NOVEMBER 9, 1964

PROFESSIONAL ENGINEER & LAND SURVEYOR UTAN LICENSE No. 1138
RIGHFIELD, UTAN

November 20, 1964

Tennaco Oil Company P. O. Box 1714 Durango, Golorado

> Re: A. J. Button Oil Unit "A"-1 Sec. 20, T. 35 S., R. 3 E., Garfield County, Utah

. .

Gent lemen:

Insofar as this office is concerned, approval to drill the above well is hereby granted.

As soon as you have determined that it will be necessary to plug and abandon this well, you are hereby requested to immediately notify the following.

PAUL W. BURCHELL, Chief Petroleum Engineer Office: DA 8-5771, DA 8-5772 or DA 8-5773 Home: CR 7-2890 Salt Lake City, Utah

This approval terminates within 90 days if this well has not been spudded within said period.

Enclosed please find Form OGCC-8-X, which is to be completed if water sands (aquifers) are encountered while drilling, particularly assessable near surface water sands. Your cooperation with respect to completing this form will be greatly appreciated.

Very truly yours,

OIL & GAS CONSERVATION COMMISSION

CLEON B. PRIGHT EXECUTIVE DIRECTOR

CBF: sch

cc: Harvey L. Coonts, Pet. Eng. Box 266, Moab, Utah



TENNECO OIL COMPANY • P. O. BOX 1714 • 835 SECOND AVENUE • DURANGO, COLORADO 81302

December 1, 1964

Miss Kathy G. Warner, Records Clerk The State of Utah Oil & Gas Conservation Commission 348 East South Temple Suite 301 Salt Lake City, Utah

Dear Miss Warner:

It is our desire to hold all information on the A. J. Button Oil Unit "A" #1 in Section 20, T-35-S, R-3-E, Garfield County, Utah, confidential.

We appreciate your calling this to our attention.

Very truly yours,

TENNECO OIL COMPANY

District Office Supervisor

JHW:sg

	Х	

SALT LAKE CITY, UTAH

Fee and PatentedState	_
Lease No	•••••
Public DomainLease No	
Indian	

Notice of Inte Notice of Inte Notice of Inte	ntion to Drill ention to Change Plans. ention to Redrill or Rep ention to Pull or Alter (ention to Abandon Well	airCasing	Subsequent R Subsequent R Supplementar	Report of Alto Report of Rec ry Well Histo	ater Shut-offdring Casingdrilling or Repairdory
	(INDICATE	LBOVE BY CHECK MARK N	ATURE OF REPORT, NOTICE		
A. J. But Well No	ton Oil Unit	660 ft. from			ember 2 , 19 64 X_{XX}^{E} line of Sec. 20
	ion 20 Sec. No.)	~	arfield	3 E (Range)	S.L.M. (Meridian) Utah
	nd plugging bond has b		A		
(State names of jobs, cementing Well spu	of and expected depths to a points, and all other impacted November 26.	objective and sho portant ork surface 1964. Drille	te formation, and dated $9-7/8$ " hole	to 210' ar	nd reamed to 15".
(State names of jobs, cementing Well spur Ran 6 jt 225 sack	of and expected depths to g g points, and all other imp	objective and sho cortant work surface 1964. Drille and 40#, J-55	ed 9-7/8" hole casing. Land	te anticipate sp to 210° ar led at 207°	pudding-in.) nd reamed to 15". '. Cemented with
(State names of jobs, cementing Well spur Ran 6 jt 225 sack	of and expected depths to a points, and all other impadded November 26, as 10-3/4", 32.75# as Class "A" cement	objective and sho cortant work surface 1964. Drille and 40#, J-55	ed 9-7/8" hole casing. Land	te anticipate sp to 210° ar led at 207°	pudding-in.) nd reamed to 15". '. Cemented with
(State names of jobs, cementing) Well spur Ran 6 jt 225 sack 750 psi,	of and expected depths to a points, and all other implied ded November 26, as 10-3/4", 32.75# as Class "A" cement held ok. Now dri	objective and sho cortant ork surface 1964. Drille and 40#, J-55 c. Circulated Illing ahead.	w sizes, weights, and ce formation, and dated 9-7/8" hole casing. Land to surface.	te anticipate sp to 210' ar led at 207' Tested cas	pudding-in.) nd reamed to 15". '. Cemented with sing and BOP to
(State names of jobs, cementing) Well spur Ran 6 jt 225 sack 750 psi,	of and expected depths to a points, and all other implied ded November 26, as 10-3/4", 32.75# as Class "A" cement held ok. Now dri	objective and show or and surface and 40#, J-55 c. Circulated alling ahead.	w sizes, weights, and ce formation, and dated 9-7/8" hole casing. Land to surface.	te anticipate sp to 210' ar led at 207' Tested cas	pudding-in.) nd reamed to 15". '. Cemented with
(State names of jobs, cementing Well spu Ran 6 jt 225 sack 750 psi,	of and expected depths to a points, and all other implied ded November 26, as 10-3/4", 32.75# as Class "A" cement held ok. Now dri	objective and show or and surface and 40#, J-55 c. Circulated alling ahead.	w sizes, weights, and ce formation, and dated 9-7/8" hole casing. Land to surface.	te anticipate sp to 210' ar led at 207' Tested cas	pudding-in.) nd reamed to 15". '. Cemented with sing and BOP to

INSTRUCTIONS: A plat or map must be attached to this form showing the location of all leases, property lines, drilling and producing wells, within an area of sufficient size so that the Commission may determine whether the location of the well conforms to applicable rules, regulations and orders.

 	n	

	1	
	 -	
 <u> </u>		_
 	x	

SALT LAKE CITY, UTAH

Fee and Patented	
State	
Lease No	
Public Domain	
Lease No	
Indian	
Lease No.	

Notice of Intention to Drill Notice of Intention to Change I Notice of Intention to Redrill o Notice of Intention to Pull or A Notice of Intention to Abandor	Plansr RepairAlter Casing	Subseque Subseque Suppleme	nt Report of nt Report of entary Well	f Altering f Redrillin History	hut-off Casing ng or Repair	
(INI	DICATE ABOVE BY CHECK MARK N				, 106h	10 6/4
Button "A"					, 1964	
Well Nois loca	ated660 ft, from	${N \atop S}$ line and	1980 ft.	from {E	line of Sec.	20
SE 1 Sec. 20 (1/4 Sec. and Sec. No.)	35 -8		3 -E		SIM	
			(Range)		(Meridia	•
Wildcat (Field)	Ga. (Cour	rileld			Utah (State or Territory)	
A drilling and plugging bond (State names of and expected dep- jobs, cementing points, and all other	has been filed with	LS OF WORK	s, and lengths	of proposed	l casings; indics ng-in.)	te mudding
A drilling and plugging bond (State names of and expected dep-	ths to objective sans; shows important work, surfact from under 10-3	LS OF WORK ow sizes, weight ace formation, and	s, and lengths ad date anticipe pipe to	pate spudding T.D. of mented 2	ng-in.) 4275'. Ra 250 sacks c	n ement
A drilling and plugging bond (State names of and expected depitors, cementing points, and all other depitors) Drilled 9-7/8" hole out 133 jts. of 7-5/8" 26. and circulated. Tester	ths to objective sans; shower important work, surfact from under 10-3.4# J-55 casing lated casing and B.O.	LS OF WORK ow sizes, weight are formation, and the surface anded at 427 P. to 500 F	s, and lengths od date anticipate pipe to 5' and ce	pate spuddin T.D. of mented 2 OK. Now	4275'• Ra 4275'• Ra 250 sacks c	n ement ahead.
A drilling and plugging bond (State names of and expected depitors, cementing points, and all other depitors) Drilled 9-7/8" hole out 133 jts. of 7-5/8" 26. and circulated. Tester	ths to objective sants; shower important work, surfact from under 10-3.4# J-55 casing lated casing and B.O.	LS OF WORK ow sizes, weight are formation, and the surface anded at 427 P. to 500 F	s, and lengths od date anticipate pipe to 5' and ce	pate spuddin T.D. of mented 2 OK. Now	4275'• Ra 4275'• Ra 250 sacks c	n ement ahead.
A drilling and plugging bond (State names of and expected depitors, cementing points, and all other depitors) Drilled 9-7/8" hole out 133 jts. of 7-5/8" 26. and circulated. Tester	ths to objective sants; shower important work, surfact from under 10-3. H J-55 casing lated casing and B.O.	LS OF WORK ow sizes, weight are formation, and the surface anded at 427 P. to 500 F	s, and lengths od date anticipate pipe to 5' and ce	pate spuddin T.D. of mented 2 OK. Now	4275'• Ra 4275'• Ra 250 sacks c	n ement ahead.

INSTRUCTIONS: A plat or map must be attached to this form showing the location of all leases, property lines, drilling and producing wells, within an area of sufficient size so that the Commission may determine whether the location of the well conforms to applicable rules, regulations and orders.

(SUBMIT	IN	niidi	TC ATEN
COLIDIALI	117	DULL	

_	_		_
1	•	AI I	٦.

1		Х	l I

SALT LAKE CITY, UTAH

Fee and Patented	
State	
Lease No	
Public Domain	
Lease No	
Indian	
Lease No.	

Otice of Int	ention to Drill		Subsequent 1	Report of Wa	ater Shut-off
	tention to Change Pla				ering Casing
	tention to Redrill or I		1	•	drilling or Repair
	tention to Pull or Alt	_	Supplementa	ry Well Hist	ory
lotice of Int	tention to Abandon V	Vell			
	(INDICA	ATE ABOVE BY CHECK MARK NA			_
Ŧ	Sutton "A"			January /	22 , 19 . 65
Well No	is locate	ed $.660$ ft, from	${\bf S}$ line and ${\bf L}$	980. ft. from	$\left\{ \begin{array}{l} \mathbf{E} \\ \mathbf{W} \end{array} \right\}$ line of Sec. 20
SE ½ Sec.	. 20	35 -s		≯ E	SIM
	nd Sec. No.)	(Twp.)		(Range)	(Meridian)
Wildca	(Field)	Garfield	or Subdivision		Utah (Siate or Territory)
State names	and plugging bond has s of and expected depths	DET IL.	OF WORK	d lengths of pr	roposed casings; indicate muddi
(State names jobs, cementi Drilled of 15# and 1 overall) cement wa	s of and expected depths ing points, and all other out from under 7- 3# J-55 casing 1 Cemented w/155 ater. Drilled ou	DET.IL. to objective sands, shiw important work, surface 5/8" casing at 42 iner w/liner hang sacks Class C cen	v sizes, weights, and formation, and de 275' w/6-3/4" ger at 3860' ment with no	ate anticipate s hole to 5 and landed returns to	roposed casings; indicate muddispudding-in.) 093'. Ran 39 jts. of at 5090'. (Ran 1230 surface, reversed ou o psi OK. Now testing
(State names jobs, cementi Drilled of 15# and 1 overall) cement wa	s of and expected depths ing points, and all other out from under 7- 3# J-55 casing 1 Cemented w/155	DET.IL. to objective sands, shiw important work, surface 5/8" casing at 42 iner w/liner hang sacks Class C cen	v sizes, weights, and formation, and de 275' w/6-3/4" ger at 3860' ment with no	ate anticipate s hole to 5 and landed returns to	opudding-in.) 093'• Ran 39 jts• of at 5090'• (Ran 1230 surface, reversed ou
(State names jobs, cementi Drilled colf and loverall) cement wa	s of and expected depths ing points, and all other out from under 7- 3# J-55 casing 1 Cemented w/155 ater. Drilled ou	DET.IL. to objective sands, shiw important work, surface 5/8" casing at 42 iner w/liner hang sacks Class C cen	v sizes, weights, and formation, and de 275' w/6-3/4" ger at 3860' ment with no	ate anticipate s hole to 5 and landed returns to	opudding-in.) 093'• Ran 39 jts• of at 5090'• (Ran 1230 surface, reversed ou
(State names jobs, cementi Drilled colf and loverall) cement wa	s of and expected depths ing points, and all other out from under 7- 3# J-55 casing 1 Cemented w/155 ater. Drilled ou	DET.IL. to objective sands, shiw important work, surface 5/8" casing at 42 iner w/liner hang sacks Class C cen	v sizes, weights, and formation, and de 275' w/6-3/4" ger at 3860' ment with no	ate anticipate s hole to 5 and landed returns to	opudding-in.) 093'• Ran 39 jts• of at 5090'• (Ran 1230 surface, reversed ou
(State names jobs, cementi Drilled of 15# and 1 overall) cement wa	s of and expected depths ing points, and all other out from under 7- 3# J-55 casing 1 Cemented w/155 ater. Drilled ou	DET.IL. to objective sands, shiw important work, surface 5/8" casing at 42 iner w/liner hang sacks Class C cen	v sizes, weights, and formation, and de 275' w/6-3/4" ger at 3860' ment with no	ate anticipate s hole to 5 and landed returns to	opudding-in.) 093'• Ran 39 jts• of at 5090'• (Ran 1230 surface, reversed ou
(State names jobs, cementi Drilled colf and loverall) cement wa	s of and expected depths ing points, and all other out from under 7- 3# J-55 casing 1 Cemented w/155 ater. Drilled ou	DET.IL. to objective sands, shiw important work, surface 5/8" casing at 42 iner w/liner hang sacks Class C cen	v sizes, weights, and formation, and de 275' w/6-3/4" ger at 3860' ment with no	ate anticipate s hole to 5 and landed returns to	opudding-in.) 093'• Ran 39 jts• of at 5090'• (Ran 1230 surface, reversed ou
(State names jobs, cementi Drilled of 15# and 1 overall) cement wa zone 4907	s of and expected depths ing points, and all other out from under 7-3# J-55 casing 1 Cemented w/155 ater. Drilled out to 5026'.	to objective sands, shi we important work, surface 5/8" casing at 42 iner w/liner hang sacks Class C cent cement to 5060"	v sizes, weights, and a formation, and de 275' w/6-3/4" ger at 3860' ment with no de tested cas	hole to 50 and landed returns to ing to 1000	opudding-in.) 093'. Ran 39 jts. of at 5090'. (Ran 1230) surface, reversed ou o psi OK. Now testin
(State names jobs, cementi Drilled of 15# and 1 overall) cement was zone 4907	s of and expected depths ing points, and all other out from under 7-3# J-55 casing 1 Cemented w/155 ater. Drilled out to 5026.	to objective sands, shi we important work, surface 5/8" casing at 42 iner w/liner hang sacks Class C cent cement to 5060"	v sizes, weights, and a formation, and de 275' w/6-3/4" ger at 3860' ment with no de tested cas	hole to 50 and landed returns to ing to 1000	opudding-in.) 093'• Ran 39 jts• of at 5090'• (Ran 1230 surface, reversed ou
(State names jobs, cementi Drilled of 15# and 1 overall) cement wa zone 4907	s of and expected depths ing points, and all other out from under 7-3# J-55 casing 1 Cemented w/155 ater. Drilled out to 5026'.	to objective sands, shi we important work, surface 5/8" casing at 42 iner w/liner hang sacks Class C cent cement to 5060"	v sizes, weights, and a formation, and de 275' w/6-3/4" ger at 3860' ment with no de tested cas	hole to 50 and landed returns to ing to 1000	opudding-in.) 093'. Ran 39 jts. of at 5090'. (Ran 1230) surface, reversed ou o psi OK. Now testin

INSTRUCTIONS: A plat or map must be attached to this form showing the location of all leases, property lines, drilling and producing wells, within an area of sufficient size so that the Commission may determine whether the location of the well conforms to applicable rules, regulations and orders.

-CONFIDENTIAL -

PLUGGING PROGRAM FORM

Name of Company Lonnect Verbal Approval Given To: Let Saston
Well Name: AJ. Sutter # / Sec. 20 T. 35 SR. 3 E County: Hayfuld
Verbal Approval was given to plug the above mentioned well in the following manner:
T.D 5093 78 m at 4275 5 Planeis : 690 (Coment from
bond log 4 90 0 32 lash 600 5020 - 4900 Part. 4926 -> 32 lash 5020 -> 4900
5020-5000000000000000000000000000000000
in 78 obert 900/ comet - langer at 3866
Water - Mayor & Chinhi > 2907 - wellow
2000
(4) 103/ 1 Et farmer desert went
Date Verbally Approv. File 1, 5 Signed: Laul W. Burchell



TENNECO OIL COMPANY · P. O. BOX 1714 · 835 SECOND AVENUE · DURANGO, COLORADO 81302

February 9, 1965

CONFIDENTIAL

The State of Utah Oil & Gas Conservation Commission 348 East South Temple Suite 301 Salt Lake City, Utah

Attention: Mr. P. W. Burchell

Gentlemen:

Re: A. J. Button "A" No. 1 Section 20, T. 35 S., R. 3 E. Garfield County, Utah

Confirming your telephone conversation of recent date with Mr. Lee Saxton regarding the plugging of the subject well.

Please find attached "Notice of Intention to Abandon Well", Notice of Well Abandonment" and Report of Water Encountered During Drilling.

Yours very truly,

TENNECO OIL COMPANY

District Office Supervisor

GAF:bjo

Attach.

ĺ	XX	

SALT LAKE CITY. UTAH

Fee and Patented	□xx
State	
Lease No	
Public Domain	
Lease No	
Indian	
Lease No	

SUNDRY NO	OTICES AND	D REPORTS O	N WELLS
Notice of Intention to Drill	pair	Subsequent Report of A Subsequent Report of F Supplementary Well Hi	Vater Shut-offRedrilling or Repairstory
(INDICATE	ABOVE BY CHECK MARK NATI	JRE OF REPORT, NOTICE, OR OTHER DA	NTA)
A. J. Button "A" Well No is located	•	line and .1980 ft. fro	•
SE/4 Section 20 (1/4 Sec. and Sec. No.)	35.S. (Twp.)	3 E (Range)	S.L.M. (Meridian)
Wildcat	Garí	rield .	Utah
The elevation of the derivation from A drilling and plugging bond has	evel above sea level is		(State or Territory)
(State names of and expected depths to jobs, cementing points, and all other im Well drilled to T.D. of 5060 abandon well as follows:	objective sands; show nportant work, surface	formation, and date anticipate	e spudding-in.)
Set cast iron bridge plug at plug from 5010-4250 feet. Of sack cement plug from 1732-off casing 8 feet below growsack cement plug in top of 1	Cut off 7-5/8" o 1622. Set 50 se und level as per 10-3/4" surface	easing at 1732' and p acks cement plug from r agreement with land casing.	oull casing. Set 60 1 1000-900. Cut
	CONTI	DENTIAL	
I understand that this plan of work mu	st receive approval in	writing by the Commission be	fore operations may be commenced.
Company Tenneco Oil Comp	any		g
Address P. O. Box 1714		By All	Thems
Durango, Colorad		Title District Office	J.H.Watkins Supervisor
INSTRUCTIONS: A plat or map mus		orm showing the location of al	ll leases, property lines, drilling and

INSTRUCTIONS: A plat or map must be attached to this form showing the location of all leases, property lines, drilling and producing wells, within an area of sufficient size so that the Commission may determine whether the location of the well conforms to applicable rules, regulations and orders.

_	_		_	
Ŧ		R.T	m	

 	 xx	

SALT LAKE CITY, UTAH

Fee and Patented
State
Lease No
Public Domain
Lease No
Indian
Lagge No

SUNDRY N	OTICES AN	D REPORTS ON	WELLS
Notice of Intention to Drill		Subsequent Report of Wa	iter Shut-off
lotice of Intention to Change Plan	ns		ering Casing
lotice of Intention to Redrill or R			drilling or Repair
lotice of Intention to Pull or Alte		Supplementary Well Hist	ory
otice of Intention to Abandon W	ell		Abandonment
, NA		TURE OF REPORT, NOTICE, OR OTHER DATA	
(INDICA	E ABOVE BY CHECK HARR HA		, ary 9, 1965
A T Button "A"	_		
A. J. Button "A" Well Nol is located	660 ft from	$\begin{array}{c} \mathbf{N} \\ \mathbf{S} \end{array}$ line and $\begin{array}{c} 1980 \\ \end{array}$ ft. from	line of Sec. 20
SE/4 Section 20	35 S	3.E	S.L.M.
	• • •		
Wildcat (Field)	Gari	Cield	Utah (State or Territory)
ground lev	el		(2.2.0 2. 2,
The elevation of the decrick flag	r above sea level is	5786 feet.	
A drilling and plugging bond has	s been filed with		•
		a on work	
		S OF WORK	
(State names of and expected depths jobs, cementing points, and all other i	to objective sands; show mportant work, surface	v sizes, weights, and lengths of pr e formation, and date anticipate s	oposed casings; indicate muddin pudding-in.)
Well abandoned as follows:			
Set cast iron bridge plug plug from 5010-4250 feet. 60 sack cement plug from 1 off casing 8 feet below gr surface casing.	Cut off 7-5/8" 732-1622. Set 5	casing at 1732' and pu	lled casing. Set n 1000-900. Cut
	1111311	DENTIAL	
	CUNT	DENIIAL	
I understand that this plan of work n	nust receive approval in	writing by the Commission before	re operations may be commenced
Company Tenneco Oil Com	pany		· <u>-</u>
Address P. O. Box 1714		By 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	mo
Durango, Colora	do	Title District Office	J. H. Watkins Supervisor
<u> </u>		11010	<u></u>

INSTRUCTIONS: A plat or map must be attached to this form showing the location of all leases, property lines, drilling and producing wells, within an area of sufficient size so that the Commission may determine whether the location of the well conforms to applicable rules, regulations and orders.

STATE OF UTAH

OIL & GAS CONSERVATION COMMISSION

Salt Lake City, Utah

Тα	he	kent	Confidential	until	
		корт		(Not to exceed 4 months after filing dat	e

LOG OF OIL OR GAS WELL

				_		D 0 D	3 (73)		Q-33-
						s P. O. Box			
						Wildcat			
						Cor	-		
Location	on660	. ft. $\left oldsymbol{ iny KX} ight oldsymbol{ iny KX}$ of $\mathbb S$	Line aı	1980 t	$\mathbf{t}. \begin{bmatrix} \mathbf{X} \mathbf{X} \\ \mathbf{W} \end{bmatrix} $ of \mathbf{E} .	Line of		Eleva	tion 5796
T	he inform		erewith is	a complailable re	ete and corrected	et record of the w	ell and all	l work de	one thereon
Date .	2-1	0-65				Title			
T	he summa	ry on this pa	ge is for t	he condit	tion of the wel	l at above date.			
Comm	enced dril	llingNo	vember 2	26 , , 1	964 Finish	ned drillingJ	anuary 4		, 19.65.
			OI		AS SANDS (Denote gas by G)				
No. 1,	from	4306	to432	21D	ry. No. 4	, from4924	to	4930	O Dry
No. 2,	from	4342	to 435	52 D:	ry. No. 5	, from4973	to	499	L Dry
No. 3,	from	4904	to491	O D	ry No. 6,	, from5037.	to	504	2 Dry
·			I	MPORT.	ANT WATER	SANDS			
No. 1,	from	NONE				, from	to	·	
No. 2,	from		_ to		No. 4	, from	to		
·					SING RECO	RD			
Size	Weight per foot	Threads per	Make	Amount	Kind of shoe	Cut and pulled from	Perfor	ated	Purpose
casing	per foot	Inch			- Allia di giloe	Cut and puned from	From-		rurpose
•••••									
			MUDD	ING AN		ING RECORD			
Size	Where se	et Numb	er sacks of ce	ment	Method used	Mud gravity	Am	nount of mu	ıd used
casing		·					-		
								· · · · · · · · · · · · · · · · · · ·	
			**********	·					
							'		

Size Shell used		Explosive used	luantity Date	Depth shot	Depth cleaned out
			OLS USED	1.6	
•					feet tofeet
able tools	were used from	feet to		, and from	feet to feet
nato D& A	February	6. 19.6	DATES 5 Put to pro-	ducing	, 19
		•	_		·
-			Darreis o		% was oil;%
•	% water; and			• .	
If gas v	vell, cu. ft. per 24	hours	Gallons gas	oline per 1,000 cu	. ft. of gas
Rock p	ressure, lbs. per s	q. in			
			IPLOYEES		T) 111
		, Driller			, Driller
		, Driller			, Driller
		FORMA	TION RECORI		
FROM-	то	TOTAL FEET		FORMATI	ON
				of complete Driller's whether from Electri	Log add Geologic Tops. c Logs or samples.
0	828	828	Carmel -	Siltstone & sl	nale w/interbedded sand
0.00	906	78	Navajo -		ets tongue. Sandstone w
828	Į.				ighte.
906	948	42	Carmel -	Judd Hollow To bedded siltsto	ongue. Shale with inter
906 948	2987	2039	Navajo -	bedded s iltst o Sandstone w/ir	ongue. Shale with inter one. nterbedded siltstones.
906 948 987	29 87 3455	2039 468	Navajo - Chinle -	bedded siltsto Sandstone w/ir Shale with int	ongue. Shale with inter one. nterbedded siltatones. terbedded sandstones.
906 948 987 8455	2987 3455 3747	2039 468 292	Navajo - Chinle - Shinarump	bedded siltsto Sandstone w/in Shale with int - Sandstone v	ongue. Shale with inter one. nterbedded siltctones. terbedded sandstones. w/interbedded shale.
906 948 987 9455 8747	2987 3455 3747 4280	2039 468 292 533	Navajo - Chinle - Shinarump Moenkopi	bedded siltsto Sandstone w/in Shale with int - Sandstone w - Shale w/intedolomite.	ongue. Shale with inter one. nterbedded siltctones. terbedded sandstones. w/interbedded shale. erbedded sandstone and
906 948 2987 1455 1747	2987 3455 3747 4280 4670	2039 468 292 533 390	Navajo - Chinle - Shinarump Moenkopi Kaibab -	bedded siltsto Sandstone w/in Shale with int - Sandstone w - Shale w/intedolomite. Dolomite w/inte	ongue. Shale with interpone. nterbedded siltctones. terbedded sandstones. y/interbedded shale. erbedded sandstone and terbedded sandstone.
906 948 2987 1455 1747	2987 3455 3747 4280	2039 468 292 533	Navajo - Chinle - Shinarump Moenkopi Kaibab -	bedded siltsto Sandstone w/in Shale with ind - Sandstone w - Shale w/intedolomite. Dolomite w/ind - Dolomite & s	ongue. Shale with inter one. nterbedded siltctones. terbedded sandstones. w/interbedded shale. erbedded sandstone and
906 948 2987 3455 3747 4280 4670	2987 3455 3747 4280 4670	2039 468 292 533 390	Navajo - Chinle - Shinarump Moenkopi Kaibab - Toroweap	bedded siltsto Sandstone w/in Shale with int - Sandstone w - Shale w/intedolomite. Dolomite w/inte	ongue. Shale with interpone. nterbedded siltctones. terbedded sandstones. w/interbedded shale. erbedded sandstone and terbedded sandstone. sandstone w/interbedded
906 948 2987 8455 8747 4280	2987 3455 3747 4280 4670 5030	2039 468 292 533 390 360	Navajo - Chinle - Shinarump Moenkopi Kaibab - Toroweap	bedded siltsto Sandstone w/in Shale with ind - Sandstone w - Shale w/inte dolomite. Dolomite w/ind - Dolomite & a Anhydrite.	ongue. Shale with interpone. nterbedded siltctones. terbedded sandstones. w/interbedded shale. erbedded sandstone and terbedded sandstone. sandstone w/interbedded
906 948 2987 8455 8747 4280 4670	2987 3455 3747 4280 4670 5030	2039 468 292 533 390 360	Navajo - Chinle - Shinarump Moenkopi Kaibab - Toroweap	bedded siltsto Sandstone w/in Shale with ind - Sandstone w - Shale w/inte dolomite. Dolomite w/ind - Dolomite & a Anhydrite.	ongue. Shale with interpone. nterbedded siltctones. terbedded sandstones. w/interbedded shale. erbedded sandstone and terbedded sandstone. sandstone w/interbedded
906 948 2987 8455 8747 4280 4670	2987 3455 3747 4280 4670 5030	2039 468 292 533 390 360	Navajo - Chinle - Shinarump Moenkopi Kaibab - Toroweap	bedded siltsto Sandstone w/in Shale with ind - Sandstone w - Shale w/inte dolomite. Dolomite w/ind - Dolomite & a Anhydrite.	ongue. Shale with interpone. nterbedded siltctones. terbedded sandstones. w/interbedded shale. erbedded sandstone and terbedded sandstone. sandstone w/interbedded
906 948 2987 8455 8747 4280	2987 3455 3747 4280 4670 5030	2039 468 292 533 390 360	Navajo - Chinle - Shinarump Moenkopi Kaibab - Toroweap	bedded siltsto Sandstone w/in Shale with ind - Sandstone w - Shale w/inte dolomite. Dolomite w/ind - Dolomite & a Anhydrite.	ongue. Shale with interpone. nterbedded siltctones. terbedded sandstones. w/interbedded shale. erbedded sandstone and terbedded sandstone. sandstone w/interbedded

[OVER]

May 27, 1965

Tenneco Oil Company P. O. Box 1714 Durango, Colorado 81302

Attention: Mr. J. H. Watkins, District Office Supervisor

Re: Well No. A. J. Button "A"-#1 Sec. 20, T. 35 S., R. 3 E., Garfield, County, Utah

Gentlemen:

This letter is to advise you that the "Well Completion or Recompletion Report and Log" and electric and/or radioactivity logs for the above mentioned well are due and have not been filed with this Commission as required by our rules and regulations.

Please complete the enclosed Forms OGCC-3, "Well Completion or Recompletion Report and Log", in duplicate and forward them to this office as soon as possible. If electric and/or radioactivity logs were not run, please make a statement to that effect in order to keep our records accurate and complete.

Thank you for your cooperation in this request.

Very truly yours,

OIL & GAS CONSERVATION COMMISSION

KATHY G. WARNER RECORDS CLERK

kgw

Enclosure: Forms

SIGNED

SUBMIT IN DUPLICATE* STATE OF UTAH (See other instructions or reverse side) 5. LEASE DESIGNATION AND SERIAL NO. OIL & GAS CONSERVATION COMMISSION 6. IF INDIAN, ALLOTTEE OR TRIBE NAME WELL COMPLETION OR RECOMPLETION REPORT AND LOG* 1a. TYPE OF WELL: 7. UNIT AGREEMENT NAME DRY X Other ___Dry b. TYPE OF COMPLETION: DEEP-EN NEW WELL S. FARM OR LEASE NAME Other Dry 2. NAME OF OPERATOR A. J. B. WELL NO. Button "A" Tenneco Oil Company 3. ADDRESS OF OPERATOR 10. FIELD AND POOL, OR WILDCAT P. O. Box 1714, Durango, Colorado
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* Wildcat 11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA At surface 660' FSL, 1980' FEL; Section 20, T35S, R3E At top prod. interval reported below Same At total depth Same Section 20. 12. COUNTY OR PARISH 14. PERMIT NO. DATE ISSUED Garfield Utah 19. ELEV. CASINGHEAD 15. DATE SPUDDED 16. DATE T.D. REACHED | 17. DATE COMPL. (Ready to prod.) 18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 11-26-64 1-4-65 5796' GL 5**7**96**'** Dry 20. TOTAL DEPTH, MD & TVD 23. INTERVALS ROTARY TOOLS CABLE TOOLS 21. PLUG, BACK T.D., MD & TVD 22. IF MULTIPLE COMPL., HOW MANY DRILLED BY 50601 Dry5060 WAS DIRECTIONAL SURVEY MADE 24. PRODUCING INTERVAL(S), OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)* P&A 2-6-65 Yes 26. TYPE ELECTRIC AND OTHER LOGS RUN 27. WAS WELL CORED IES, Gamma Ray-Neutron, Formation Density, Yes Bond Log. Sonic Log CASING RECORD (Report all strings set in well) 28. CEMECTING RECORD CASING SIZE WEIGHT, LB./FT DEPTH SET (MD) HOLE SIZE AMOUNT PULLED 32# & 40# None 10-3 207 9-7/8 & reamed <u> 225</u> <u>217321</u> 26.4# 4275 6-3/4 & reamed jts TUBING RECORD LINER RECORD 30. 29. SIZE BOTTOM (MD) SCREEN (MD) DEPTH SET (MD) PACKER SET (MD) SIZE TOP (MD) SACKS CEMENT* 5" 3860 5090 155 sx NONE 31. PERFORATION RECORD (Interval, size and number) ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC. 32. 4 holes/ft 4993-4907; 5025-5026. AMOUNT AND KIND OF MATERIAL USED DEPTH INTERVAL (MD) 2 holes/ft 5024-5026. 4 holes/ft 4342-52; 5024**-**26 500 gal acid 4306-21. 4819 Squeeze w/200 sx cement 4993**-**49**07** 1350 gal acid 4993-490 sx cement PRODUCTION 33.* WELL STATUS (Producing or shut-in) PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) DATE FIRST PRODUCTION Dry Dry Dry GAS-OIL BATIO DATE OF TEST HOURS TESTED CHOKE SIZE PROD'N. FOR TEST PERIOD OIL--BBL. GAS-MCF. WATER-BBL. Ha 1) 1 - CF water-BBL. FLOW. TUBING PRESS. CASING PRESSURE CALCULATED
24-HOUR RATE -BBL. GAS-MCF OIL GRAVITY-API (CORR.) 34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) TEST WITNESSED BY Dry 35. LIST OF ATTACHMENTS IES; Formation Density; Gamma Ray-Neutron; Sonic Log. State of Utah Form OGCC-3.
36. I hereby certify that the foregoly and attached information is complete and correct as determined from all available records TITLE District Office Superdisor DATE June 8, 1965

ASTRUCTIONS

or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, practicularly with regard to local, area or regional procedures and fractices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on litetis 22 and 24, and 33, below regarding separate reports for separate completions. If not filed prior to the time this summary fecord is submitted, copies of all currently available logs (drillers, geologists, sample, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

or Federal office for specific instructions.

Hem 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Hems 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 29, and in item 24 show the producing in any for only the interval in tem 33. Submit a separate report (page) on this form, adequately identified, for each and interval to be separately produced, showing the additional data pertinent to such interval.

Hem 29: "Sacks Cementing and the location of the cementing tool.

Hem 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

Continued from front of page IPem 32: Continued from front of page IPem 32: Acidized @ 4984-94 w/600 gollecte, acidized 4926-32 w/1000 gal acid. Acidized @ 4360-4295 w/1000 gal acid. Acidized @ 4306-21 w/17½ gal acid.

a.	TRUE VERT. DEPTH					
TOP	MEAS. DEPTH					
_	MEA				nces Gil Comp.	
	NAME	, 73		oo qoyunun 1 iy Tuckii 1	0. or 171%; 01 1 5, 11001	• -
					1-11-5	/\(\frac{1}{2}\)
			76	Troj.	Mina Co-ver	100
			,T.C.		()	
ETC.					ζ0-0-2 / ·	
TENTE		,EO.	onic Is	0.000 e	To Kody Carent	udi.Lç(i)
DESCRIPTION, CONTENTS, ELC.		SHEET	/2-c	203	Cd - 122	10-5/3:
SCRIPT	i ori	HED	∖ '8-8	200 1204	32 (A 4) 23. W	0/6-1. ://2-01
ā	i	TTAC				
.		₹	::: <u> </u>	(51 (1)	nt 026g	
'	- !	呂		•	. 02 - 1702/1 - 02 /	at:\nJ.[
		SEE				
	1	SEE	- (2) - (2) (2) (2) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3	.c.^(-). - d\nfo-	100 (1004-00)	le#/: t - ∩ú-(₁l.
Моли			- (27, -9, 1 7	. C. O C.		- t :\is_L -£:2-20
Begride	1 (1) (1)		<u></u>	. C. O C.	- (- (- (- (- (- (- (- (- (- (- (- (- (-	-
BOTTOM	1 (1)			. C. O C.		- # - \\ - CO
TOP BOTTION				. C. O0.		- J : \
AUL HOLLOW				. C. O		
NOTINE HOUSE	307			. C. O C.		
_	307		(noitro)			777.

STATE OF UTAH OIL & GAS CONSERVATION COMMISSION 348 EAST SOUTH TEMPLE SUITE 301 SALT LAKE CITY, UTAH

REPORT OF WATER ENCOUNTERED DURING DRILLING

Well Name &	Number: A. J. Butto	on Oil Unit "A" No. 1	
		Address P. O. Box 1714	Phone 247-5494
			tone Phone 237-2536
Contractor_	Loffland Brothers Co.	Address 5200 West Yellows Casper, Wyoming E Carrield	Country Itech
Location:	SW ½ SE ½ Sec. 20 T.	35 s R. 3 XX Garfield	County, Utah.
Water Sands	s:		
	Depth	Volume	<u>Quality</u>
_		Flow Rate or Head	Fresh or Salty
From	gettegre <mark>te</mark> n. De geleter	• • • • • • • • • • • • • • • • • • • •	
1		<u> 1886 - Harris Arrivania, martini del mar</u>	
2			
3.		and Friedrich (1997) in 1995 and the state of the state o	
		The strate of the last coard of the	programme and the second
4			
5		(continued on reverse	side if necessary)
Formation	Tops: CON	IFIDENTIAL	
Remaris:	No fresh water sand subject well.	s that yielded water were enco	ountered while drilling
NOTE: (a)		y of forms, please inform the provided for in Rule C-20, Golles of Practice and Procedure	

September 22, 1965

Tenneco Oil Company P. O. Box 1714 Durango, Colorado

> Re: Well No. A. J. Button "A"-#1, Sec. 20, T. 35 S., R. 3 E., Garfield County, Utah.

Gentlemen:

We are in receipt of the Induction-Electrical, Gamma Ray Neutron, Sonic Log and Formation Density Log for the above mentioned well. However, on your "Well Completion or Recompletion Report and Log", we note that you ran other logs which we have not received.

We would appreciate it very much if you would forward said logs as soon as possible. Thank you for your cooperation in this matter.

Very truly yours,

OIL & GAS CONSERVATION COMMISSION

SHARON C. HUNT RECORDS CLERK

sch

COMMISSIONERS . . .

B. H. CROFT CHAIRMAN

C. R. HENDERSON

C. S. THOMSON

M. V. HATCH

J. H. REESE

EXECUTIVE DIRECTOR
C. B. FEIGHT



THE STATE OF UTAH

OIL & GAS CONSERVATION COMMISSION

348 EAST SOUTH TEMPLE SUITE 301 SALT LAKE CITY, UTAH 84111

DAvis 8-5771

September 22, 1965

PETROLEUM ENGINEERS

PAUL W. BURCHELL
CHIEF ENGINEER

HARVEY L. COONTS
SALT LAKE CUTY

Tenneco Oil Company P. O. Box 1714 Durango, Colorado

> Re: Well No. A. J. Button "A"-#1, Sec. 20, T. 35 S., R. 3 E.,

Garfield County, Utah.

Hunt.

Gentlemen:

We are in receipt of the Induction-Electrical, Gamma Ray-Neutron, Sonic Log and Formation Density Log for the above mentioned well. However, on your "Well Completion or Recompletion Report and Log", we note that you ran other logs which we have not received.

We would appreciate it very much if you would forward said logs as soon as possible. Thank you for your cooperation in this matter.

Very truly yours,

OIL & GAS CONSERVATION COMMISSION

SHARON C. HUNT RECORDS CLERK

sch

TGT 2930 - 10/62 MESSAGE — REPLY **REPLY** DATE